

217/785-1705

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT -- NSPS SOURCE
REVISED

PERMITTEE

International Paper Company
Attn: Mr. Roger Knapp
100 East Oakton Street
Des Plaines, Illinois 60018

| | |
|--|---|
| Application No.: 73050433 | I.D. No.: 031063ADM |
| <u>Applicant's Designation:</u> | <u>Date Received:</u> January 24, 2014 |
| Subject: International Paper - Des Plaines Facility | |
| <u>Date Issued:</u> March 11, 2014 | <u>Expiration Date:</u> February 26, 2023 |
| <u>Location:</u> 100 East Oakton Street, Des Plaines, Cook County, 60018 | |

This Permit is hereby granted to the above-designated Permittee to OPERATE emission source(s) and/or air pollution control equipment consisting of two (2) flexographic printing/slotting/folding/gluing machines controlled by cyclones and baghouses, a folder/gluer, five (5) laminators, one (1) starch storage silo controlled by a baghouse and one (1) 29.3 mmBtu/hour natural gas-fired boiler pursuant to the above-referenced application. This Permit is subject to standard conditions attached hereto and the following special condition(s):

1a. This federally enforceable state operating permit is issued:

- i. To limit the emissions of air pollutants from the source to less than major source thresholds (i.e., 100 tons/year for Volatile Organic Material (VOM), 10 tons/year for any single Hazardous Air Pollutant (HAP) and 25 tons/year for any combination of such HAPs). As a result, the source is excluded from the requirements to obtain a Clean Air Act Permit Program (CAAPP) permit. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.
- ii. To establish federally enforceable production and operating limitations, which restrict a potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP), and 25 tons/year of any combination of such HAPs so that the source is not being subject to the requirements of the National Emission Standards for Hazardous Air Pollutants (NESHAP) for the Printing and Publishing Industry, 40 CFR 63 Subpart KK.
- iii. To limit the potential emissions of VOM from the source to less than 25 tons/year. As a result, the source is excluded from the requirement of 35 Ill. Adm. Code Part 205, Emission Reduction Market System. The maximum emissions of this source, as limited by the conditions of this permit, are described in Attachment A.

- iv. To establish federally enforceable production and operating limitations, which restrict the potential to emit for VOM to less than 25 tons per year so that the flexographic presses at this source are not subject to the requirements of 35 Ill. Adm. Code 218 Subpart H: Printing and Publishing.
- v. To establish federally enforceable production and operating limitations, which restrict the potential to emit for VOM to less than 25 tons per year so that the source is not subject to the requirements of 35 Ill. Adm. Code Part 218 Subpart PP (Miscellaneous Fabricated Product Manufacturing Processes).
- b. Prior to initial issuance, a draft of this permit has undergone a public notice and comment period.
- c. This permit supersedes all operating permit(s) for this location.
- 2. The 29.3 mmBtu/hour natural gas-fired boiler is subject to the New Source Performance Standards (NSPS) for Small Industrial - Commercial - Institutional Steam Generating Units, 40 CFR 60, Subparts A and Dc. The Illinois EPA is administering the NSPS in Illinois on behalf of the United States EPA under a delegation agreement.
- 3a. Pursuant to 35 Ill. Adm. Code 212.123(a), no person shall cause or allow the emission of smoke or other particulate matter, with an opacity greater than 30 percent, into the atmosphere from any emission unit other than those emission units subject to 35 Ill. Adm. Code 212.122.
- b. Pursuant to 35 Ill. Adm. Code 212.123(b), the emission of smoke or other particulate matter from any such emission unit may have an opacity greater than 30 percent but not greater than 60 percent for a period or periods aggregating 8 minutes in any 60 minute period provided that such opaque emissions permitted during any 60 minute period shall occur from only one such emission unit located within a 305 meter (1000 foot) radius from the center point of any other such emission unit owned or operated by such person, and provided further that such opaque emissions permitted from each such emission unit shall be limited to 3 times in any 24 hour period.
- c. Pursuant to 35 Ill. Adm. Code 212.301, no person shall cause or allow the emission of fugitive particulate matter from any process, including any material handling or storage activity, that is visible by an observer looking generally toward the zenith at a point beyond the property line of the source.
- d. Pursuant to 35 Ill. Adm. Code 212.321(a), except as further provided in 35 Ill. Adm. Code Part 212, no person shall cause or allow the emission of particulate matter into the atmosphere in any one hour period from any new process emission unit which, either alone or in combination with the emission of particulate matter from all other similar process emission units for which construction or modification commenced on or

after April 14, 1972, at a source or premises, exceeds the allowable emission rates specified in 35 Ill. Adm. Code 212.321(c).

4. Pursuant to 35 Ill. Adm. Code 216.121, no person shall cause or allow the emission of carbon monoxide (CO) into the atmosphere from any fuel combustion emission source with actual heat input greater than 2.9 MW (10 mmBtu/hour) to exceed 200 ppm, corrected to 50 percent excess air.
5. Pursuant to 35 Ill. Adm. Code 218.301, no person shall cause or allow the discharge of more than 3.6 kg/hour (8 lbs/hour) of organic material into the atmosphere from any emission unit, except as provided in 35 Ill. Adm. Code 218.302, 218.303, or 218.304 and the following exception: If no odor nuisance exists the limitation of 35 Ill. Adm. Code 218 Subpart G shall only apply to photochemically reactive material.
- 6a. This permit is issued based upon the flexographic printing presses not being subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for the Printing and Publishing Industry, 40 CFR 63, Subpart KK. This is a result of the federally enforceable production and operating limitations, which restrict the potential to emit to less than 10 tons/year for any individual Hazardous Air Pollutant (HAP), and 25 tons/year of any combination of such HAPs.
- b. This permit is issued based on the boiler at this source not being subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for Industrial, Commercial, and Institutional Boilers Area Sources, 40 CFR 63 Subpart JJJJJJ. Pursuant to 40 CFR 63.11195(e), a gas-fired boiler as defined in 40 CFR 63 Subpart JJJJJJ are not subject to 40 CFR 63 Subpart JJJJJJ and to any requirements in 40 CFR 63 Subpart JJJJJJ.
7. Pursuant to 35 Ill. Adm. Code 212.314, 35 Ill. Adm. Code 212.301 shall not apply and spraying pursuant to 35 Ill. Adm. Code 212.304 through 212.310 and 35 Ill. Adm. Code 212.312 shall not be required when the wind speed is greater than 40.2 km/hour (25 mph). Determination of wind speed for the purposes of this rule shall be by a one-hour average or hourly recorded value at the nearest official station of the U.S. Weather Bureau or by wind speed instruments operated on the site. In cases where the duration of operations subject to this rule is less than one hour, wind speed may be averaged over the duration of the operations on the basis of on-site wind speed instrument measurements.
- 8a. This permit is issued based on the flexographic printing presses not being subject to 35 Ill. Adm. Code 218.187 (Other Industrial Solvent Cleaning Operations). Pursuant to 35 Ill. Adm. Code 218.187(a)(2)(B), notwithstanding 35 Ill. Adm. Code 218.187(a)(1) cleaning operations for emission units within the flexible package printing category shall be exempt from the requirements of 35 Ill. Adm. Code 218.187(b), (c), (d), (e), (f), and (g).

- b. This permit is issued based on the flexographic printing presses not being subject to 35 Ill. Adm. Code 218.204(c) (Paper Coating). Pursuant to 35 Ill. Adm. Code 218.204(c)(3), the paper coating limitation set forth in 35 Ill. Adm. Code 218.204(c) shall not apply to any owner or operator of any paper coating line on which flexographic, rotogravure, lithographic, or letterpress printing is performed if the paper coating line complies with the applicable emissions limitations in 35 Ill. Adm. Code 218 Subpart. In addition, screen printing on paper is not regulated as paper coating, but is regulated under 35 Ill. Adm. Code 218 Subpart TT. On and after May 1, 2011, the paper coating limitation shall also not apply to coating performed on or in-line with any digital printing press, or to size presses and on-machine coaters on papermaking machines applying sizing or water-based clays.
- c. This permit is issued based upon the flexographic printing presses not being subject to the requirements of 35 Ill. Adm. Code Part 218.401, Flexographic and Rotogravure Printing. This is a result of the federally enforceable production and operating limitations, which restrict the maximum theoretical emissions of VOM from this facility to less than 100 tons per year and the potential to emit for VOM emissions to less than 25 tons per year. Pursuant to 35 Ill. Adm. Code 218.402(a), except as otherwise provided in 35 Ill. Adm. Code 218.401, the limitations of 35 Ill. Adm. Code 218.401 apply to all flexographic and rotogravure printing lines at a subject source. Sources with flexographic and/or rotogravure printing lines are subject sources if:
 - i. Total maximum theoretical emissions of VOM from all flexographic and rotogravure printing lines (including solvents used for cleanup operations associated with flexographic and rotogravure printing lines) at the source ever exceed 90.7 Mg (100 tons) per calendar year and the flexographic and rotogravure printing lines (including solvents used for cleanup operations associated with flexographic and rotogravure printing lines) at the source are not limited to less than 90.7 Mg (100 tons) of VOM emissions per calendar year in the absence of air pollution control equipment through production or capacity limitations contained in a federally enforceable permit or a SIP revision; or
 - ii. The flexographic and rotogravure printing lines (including solvents used for cleanup operations associated with flexographic and rotogravure printing lines) at the source have a potential to emit 22.7 Mg (25 tons) or more of VOM per year.
- d. This permit is issued based on the source not being subject to the requirements of 35 Ill. Adm. Code 218 Subpart JJ (Miscellaneous Industrial Adhesives). Pursuant to 35 Ill. Adm. Code 218.900(b)(1)(H), the requirements of 35 Ill. Adm. Code 218 Subpart JJ shall not apply to miscellaneous industrial adhesive application operations associated with flexible package printing.
- e. This permit is issued based upon the laminating and gluing operations not being subject to the VOM control requirements of 35 Ill. Adm. Code

Part 218 Subpart PP: Miscellaneous Fabricated Product Manufacturing Process. This is consequence of the federally enforceable production and operating limitations, which restrict a potential to emit to less than 25 tons per year from the subject sources.

9. Pursuant to 40 CFR 60.11(d), at all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Illinois EPA or USEPA which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.
- 10a. Pursuant to 35 Ill. Adm. Code 212.306, all normal traffic pattern access areas surrounding storage piles specified in 35 Ill. Adm. Code 212.304 and all normal traffic pattern roads and parking facilities which are located on mining or manufacturing property shall be paved or treated with water, oils or chemical dust suppressants. All paved areas shall be cleaned on a regular basis. All areas treated with water, oils or chemical dust suppressants shall have the treatment applied on a regular basis, as needed, in accordance with the operating program required by 35 Ill. Adm. Code 212.309, 212.310 and 212.312.
- b. Pursuant to 35 Ill. Adm. Code 212.307, all unloading and transporting operations of materials collected by pollution control equipment shall be enclosed or shall utilize spraying, pelletizing, screw conveying or other equivalent methods.
- c. Pursuant to 35 Ill. Adm. Code 212.309(a), the emission units described in 35 Ill. Adm. Code 212.304 through 212.308 and 35 Ill. Adm. Code 212.316 shall be operated under the provisions of an operating program, consistent with the requirements set forth in 35 Ill. Adm. Code 212.310 and 212.312, and prepared by the owner or operator and submitted to the Illinois EPA for its review. Such operating program shall be designed to significantly reduce fugitive particulate matter emissions.
- d. Pursuant to 35 Ill. Adm. Code 212.310, as a minimum the operating program shall include the following:
 - i. The name and address of the source;
 - ii. The name and address of the owner or operator responsible for execution of the operating program;
 - iii. A map or diagram of the source showing approximate locations of storage piles, conveyor loading operations, normal traffic pattern access areas surrounding storage piles and all normal traffic patterns within the source;

- iv. Location of unloading and transporting operations with pollution control equipment;
 - v. A detailed description of the best management practices utilized to achieve compliance with 35 Ill. Adm. Code 212 Subpart K, including an engineering specification of particulate collection equipment, application systems for water, oil, chemicals and dust suppressants utilized and equivalent methods utilized;
 - vi. Estimated frequency of application of dust suppressants by location of materials; and
 - vii. Such other information as may be necessary to facilitate the Illinois EPA's review of the operating program.
- e. Pursuant to 35 Ill. Adm. Code 212.312, the operating program shall be amended from time to time by the owner or operator so that the operating program is current. Such amendments shall be consistent with 35 Ill. Adm. Code 212 Subpart K and shall be submitted to the Illinois EPA for its review.
- 11a. Pursuant to 35 Ill. Adm. Code 218.401(d), no owner or operator of subject flexographic or rotogravure printing lines that print flexible packaging or print flexible packaging and non-flexible packaging on the same line shall cause or allow VOM containing cleaning materials, including used cleaning towels, associated with the subject flexographic or rotogravure printing lines to be kept, stored, or disposed of in any manner other than in closed containers, or conveyed from one location to another in any manner other than in closed containers or pipes, except when specifically in use.
- b. Pursuant to 35 Ill. Adm. Code 218.402(b), the limitations of 35 Ill. Adm. Code 218.401(d) shall apply to all owners or operators of flexographic or rotogravure printing lines that print flexible packaging, or that print flexible packaging and non-flexible packaging on the same line, at a source where the combined emissions of VOM from all flexographic and rotogravure printing lines total 6.8 kg/day (15 lbs/day) or more (including solvents used for cleanup operations associated with flexographic and rotogravure printing lines), in the absence of air pollution control equipment.
- 12a. In the event that the operation of this source results in an odor nuisance, the Permittee shall take appropriate and necessary actions to minimize odors, including but not limited to, changes in raw material or installation of controls, in order to eliminate the odor nuisance.
- b. The Permittee shall, in accordance with the manufacturer(s) and/or vendor(s) recommendations, perform periodic maintenance on the cyclones and baghouses such that the cyclones and baghouses are kept in proper working condition and not cause a violation of the Illinois Environmental Protection Act or regulations promulgated therein.

- c. The boiler shall only be operated with natural gas as the fuel. The use of any other fuel in the boiler requires that the Permittee first obtain a construction permit from the Illinois EPA and then perform stack testing to verify compliance with all applicable requirements.

- 13a. Plant-wide usage of raw materials and VOM emissions, including all clean-up operations, shall not exceed the following limits:

| <u>Material</u> | <u>Usage</u> | | <u>VOM Content</u> (wt. %) | <u>VOM Emissions</u> | |
|-----------------|------------------|------------------|-------------------------------|----------------------|------------------|
| | <u>(Tons/Mo)</u> | <u>(Tons/Yr)</u> | | <u>(Tons/Mo)</u> | <u>(Tons/Yr)</u> |
| Inks | 25 | 220 | 5.0 | 1.25 | 11.00 |
| High-VOM Glue | 2 | 25 | 4.0 | 0.08 | 1.00 |
| Low-VOM Glue | 250 | 2,000 | 0.5 | 1.25 | 10.00 |
| | | | | Total: | 22.00 |

These limits define the potential emissions of VOM and are based on the maximum actual emissions determined from the maximum production capacity and VOM content of raw materials.

- b. Operation and emissions of the boiler shall not exceed the following limits:

- i. Natural gas usage: 25.2 mmscf/month, 251.6 mmscf/year
- ii. Emissions from the combustion of natural gas:

| <u>Pollutant</u> | <u>Emission Factor</u> | <u>Emissions</u> | |
|------------------------------------|------------------------|------------------|------------------|
| | <u>(lb/mmBtu)</u> | <u>(Tons/Mo)</u> | <u>(Tons/Yr)</u> |
| Carbon Monoxide (CO) | 84.0 | 1.06 | 10.57 |
| Nitrogen Oxides (NO _x) | 100.0 | 1.26 | 12.58 |
| Particulate Matter (PM) | 7.6 | 0.10 | 0.96 |
| Sulfur Dioxide (SO ₂) | 0.6 | 0.01 | 0.08 |
| Volatile Organic Material (VOM) | 5.5 | 0.07 | 0.70 |

These limits are based on maximum firing rate of 29.3 mmBtu/hour and standard emission factors (Tables 1.4-1 and 1.4-2, AP-42, Fifth Edition, Volume I, Supplement D, July 1998).

- c. This permit is issued based on negligible emissions of particulate matter from the starch storage silo. For this purpose emission shall not exceed nominal emission rate of 0.1 lb/hour and 0.44 tons/year.
- d. The emissions of Hazardous Air Pollutants (HAPs) as listed in Section 112(b) of the Clean Air Act from this source shall not exceed 0.9 tons/month and 9.0 tons/year of any single HAP and 2.25 tons/month and 22.5 tons/year of any combination of such HAPs. As a result of this condition, this permit is issued based on the emissions of any HAP from this source not triggering the requirement to obtain a CAAPP permit from the Illinois EPA and the NESHAP for Printing and Publishing Industry, 40 CFR 63 Subpart KK.

- e. Compliance with the annual limits of this permit shall be determined on a monthly basis from the sum of the data for the current month plus the preceding 11 months (running 12 month total).
- 14a. Pursuant to 35 Ill. Adm. Code 201.282, every emission source or air pollution control equipment shall be subject to the following testing requirements for the purpose of determining the nature and quantities of specified air contaminant emissions and for the purpose of determining ground level and ambient air concentrations of such air contaminants:
- i. Testing by Owner or Operator. The Illinois EPA may require the owner or operator of the emission source or air pollution control equipment to conduct such tests in accordance with procedures adopted by the Illinois EPA, at such reasonable times as may be specified by the Illinois EPA and at the expense of the owner or operator of the emission source or air pollution control equipment. The Illinois EPA may adopt procedures detailing methods of testing and formats for reporting results of testing. Such procedures and revisions thereto, shall not become effective until filed with the Secretary of State, as required by the APA Act. All such tests shall be made by or under the direction of a person qualified by training and/or experience in the field of air pollution testing. The Illinois EPA shall have the right to observe all aspects of such tests.
 - ii. Testing by the Illinois EPA. The Illinois EPA shall have the right to conduct such tests at any time at its own expense. Upon request of the Illinois EPA, the owner or operator of the emission source or air pollution control equipment shall provide, without charge to the Illinois EPA, necessary holes in stacks or ducts and other safe and proper testing facilities, including scaffolding, but excluding instruments and sensing devices, as may be necessary.
- b. Testing required by Conditions 15 and 16 shall be performed upon a written request from the Illinois EPA by a qualified independent testing service.
15. Pursuant to 35 Ill. Adm. Code 212.110(c), upon a written notification by the Illinois EPA, the owner or operator of a particulate matter emission unit subject to 35 Ill. Adm. Code Part 212 shall conduct the applicable testing for particulate matter emissions, opacity, or visible emissions at such person's own expense, to demonstrate compliance. Such test results shall be submitted to the Illinois EPA within thirty (30) days after conducting the test unless an alternative time for submittal is agreed to by the Illinois EPA.
16. Pursuant to 35 Ill. Adm. Code 218.404(a), the VOM content of each coating and ink and the efficiency of each capture system and control device shall be determined by the applicable test methods and

procedures specified in 35 Ill. Adm. Code 218.105 to establish the records required under 35 Ill. Adm. Code 218.404.

- 17a. Pursuant to 40 CFR 60.7(b), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain records of the occurrence and duration of any startup, shutdown, or malfunction in the operation of an affected facility; any malfunction of the air pollution control equipment; or any periods during which a continuous monitoring system or monitoring device is inoperative.
 - b. Pursuant to 40 CFR 60.7(f), any owner or operator subject to the provisions of 40 CFR Part 60 shall maintain a file of all measurements, including continuous monitoring system, monitoring device, and performance testing measurements; all continuous monitoring system performance evaluations; all continuous monitoring system or monitoring device calibration checks; adjustments and maintenance performed on these systems or devices; and all other information required by 40 CFR Part 60 recorded in a permanent form suitable for inspection. The file shall be retained for at least two years following the date of such measurements, maintenance, reports, and records.
- 18a.
 - i. Pursuant to 40 CFR 60.48c(g)(1), except as provided under 40 CFR 60.48c(g)(2) and (g)(3), the owner or operator of each affected facility shall record and maintain records of the amount of each fuel combusted during each operating day.
 - ii. Pursuant to 40 CFR 60.48c(g)(2), as an alternative to meeting the requirements of 40 CFR 60.48c(g)(1), the owner or operator of an affected facility that combusts only natural gas, wood, fuels using fuel certification in 40 CFR 60.48c(f) to demonstrate compliance with the SO₂ standard, fuels not subject to an emissions standard (excluding opacity), or a mixture of these fuels may elect to record and maintain records of the amount of each fuel combusted during each calendar month.
 - iii. Pursuant to 40 CFR 60.48c(g)(3), as an alternative to meeting the requirements of 40 CFR 60.48c(g)(1), the owner or operator of an affected facility or multiple affected facilities located on a contiguous property unit where the only fuels combusted in any steam generating unit (including steam generating units not subject to 40 CFR 60 Subpart Dc) at that property are natural gas, wood, distillate oil meeting the most current requirements in 40 CFR 60.42c to use fuel certification to demonstrate compliance with the SO₂ standard, and/or fuels, excluding coal and residual oil, not subject to an emissions standard (excluding opacity) may elect to record and maintain records of the total amount of each steam generating unit fuel delivered to that property during each calendar month.
 - b. Pursuant to 40 CFR 60.48c(i), all records required under 40 CFR 60.48 shall be maintained by the owner or operator of the affected facility for a period of two years following the date of such record.

19. Pursuant to 40 CFR 63.10(b)(3), if an owner or operator determines that his or her stationary source that emits (or has the potential to emit, without considering controls) one or more hazardous air pollutants regulated by any standard established pursuant to Section 112(d) or (f) of the Clean Air Act, and that stationary source is in the source category regulated by the relevant standard, but that source is not subject to the relevant standard (or other requirement established under 40 CFR Part 63) because of limitations on the source's potential to emit or an exclusion, the owner or operator must keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The record of the applicability determination must be signed by the person making the determination and include an analysis (or other information) that demonstrates why the owner or operator believes the source is unaffected (e.g., because the source is an area source). The analysis (or other information) must be sufficiently detailed to allow the USEPA and/or Illinois EPA to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis must be performed in accordance with requirements established in relevant subparts of 40 CFR Part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with USEPA guidance materials published to assist sources in making applicability determinations under Section 112 of the Clean Air Act, if any. The requirements to determine applicability of a standard under 40 CFR 63.1(b)(3) and to record the results of that determination under 40 CFR 63.10(b)(3) shall not by themselves create an obligation for the owner or operator to obtain a Title V permit.
20. Pursuant to 35 Ill. Adm. Code 212.110(e), the owner or operator of an emission unit subject to 35 Ill. Adm. Code Part 212 shall retain records of all tests which are performed. These records shall be retained for at least three (3) years after the date a test is performed.
- 21a. Pursuant to 35 Ill. Adm. Code 218.404(b)(2), any owner or operator of a printing line which is exempted from any of the limitations of 35 Ill. Adm. Code 218.401 because of the criteria in 35 Ill. Adm. Code 218.402(a) shall comply with the following: On and after a date consistent with 35 Ill. Adm. Code 218.106, or, for flexographic or rotogravure printing lines that print flexible packaging or that print flexible packaging and non-flexible packaging on the same line, on and after January 1, 2012, the owner or operator of a flexographic and rotogravure printing line referenced in this subsection shall collect and record all of the following information each year for each printing line and maintain the information at the source for a period of three years:
 - i. The name and identification number of each coating and ink as applied on each printing line.

- ii. The VOM content and the volume of each coating and ink as applied each year on each printing line.
 - b. Pursuant to 35 Ill. Adm. Code 218.404(h), all records required by 35 Ill. Adm. Code 218.404(f) and (g) shall be retained for at least three years and shall be made available to the Illinois EPA upon request.
- 22a. The Permittee shall maintain monthly records of the following items so as to demonstrate compliance with the conditions of this permit:
- i. Records addressing use of good operating practices for the cyclones and baghouses:
 - A. Records for periodic inspection of the cyclones and baghouses with date, individual performing the inspection, and nature of inspection; and
 - B. Records for prompt repair of defects, with identification and description of defect, effect on emissions, date identified, date repaired, and nature of repair.
 - ii. Names and amounts of inks, glues and other VOM or HAP containing materials used (tons/month and tons/year);
 - iii. VOM and HAP content of inks, glues and other VOM or HAP containing materials used (weight %);
 - iv. Natural gas usage (mmscf/month and mmscf/year);
 - v. Throughput for the Starch Storage Silo (tons/month and tons/year); and
 - vi. Monthly and annual emissions of CO, NO_x, PM, SO₂, VOM and HAPs from the source with supporting calculations (tons/month and tons/year).
- b. All records and logs required by this permit shall be retained at a readily accessible location at the source for at least five (5) years from the date of entry and shall be made available for inspection and copying by the Illinois EPA or USEPA upon request. Any records retained in an electronic format (e.g., computer storage device) shall be capable of being retrieved and printed on paper during normal source office hours so as to be able to respond to the Illinois EPA or USEPA request for records during the course of a source inspection.
23. Pursuant to 35 Ill. Adm. Code 212.110(d), a person planning to conduct testing for particulate matter emissions to demonstrate compliance shall give written notice to the Illinois EPA of that intent. Such notification shall be given at least thirty (30) days prior to the initiation of the test unless a shorter period is agreed to by the

Illinois EPA. Such notification shall state the specific test methods from 35 Ill. Adm. Code 212.110 that will be used.

- 24a. Pursuant to 35 Ill. Adm. Code 218.404(b)(3), any owner or operator of a printing line which is exempted from any of the limitations of 35 Ill. Adm. Code 218.401 because of the criteria in 35 Ill. Adm. Code 218.402(a) shall comply with the following: On and after a date consistent with 35 Ill. Adm. Code 218.106, or, for flexographic or rotogravure printing lines that print flexible packaging or that print flexible packaging and non-flexible packaging on the same line, on and after January 1, 2012, the owner or operator of a flexographic and rotogravure printing line exempted from the limitations of 35 Ill. Adm. Code 218.401 because of the criteria in 35 Ill. Adm. Code 218.402(a) shall notify the Illinois EPA of any record showing that total maximum theoretical emissions of VOM from all printing lines exceed 90.7 Mg (100 tons) in any calendar year before the application of capture systems and control devices, or that the combined potential to emit of all flexographic and rotogravure printing lines at the source equals or exceeds 22.7 Mg (25 tons) of VOM in any calendar year, by sending a copy of such record to the Illinois EPA within 30 days after the exceedance occurs.
- b. Pursuant to 35 Ill. Adm. Code 218.404(g)(2), any owner or operator of a printing line subject to the limitations of 35 Ill. Adm. Code 218.401(d) shall notify the Illinois EPA of any violation of 35 Ill. Adm. Code 218.401(d) by sending a description of the violation and copies of records documenting such violations to the Illinois EPA within 30 days following the occurrence of the violation.
- c. Pursuant to 35 Ill. Adm. Code 218.990, upon request by the Illinois EPA, the owner or operator of an emission unit which is exempt from the requirements of 35 Ill. Adm. Code 218 Subparts PP, QQ, RR, TT or 35 Ill. Adm. Code 218.208(b) shall submit records to the Illinois EPA within 30 calendar days from the date of the request that document that the emission unit is exempt from those requirements.
- 25a. If there is an exceedance of or a deviation from the requirements of this permit as determined by the records required by this permit, the Permittee shall submit a report to the Illinois EPA's Compliance Section in Springfield, Illinois within 30 days after the exceedance or deviation. The report shall include the emissions released in accordance with the recordkeeping requirements, a copy of the relevant records, a description of the exceedances or deviation, and efforts to reduce emissions and future occurrences.
- b. Two (2) copies of required reports and notifications shall be sent to:

Illinois Environmental Protection Agency
Division of Air Pollution Control
Compliance Section (#40)
P.O. Box 19276
Springfield, Illinois 62794-9276

and one (1) copy shall be sent to the Illinois EPA's regional office at the following address unless otherwise indicated:

Illinois Environmental Protection Illinois EPA
Division of Air Pollution Control
9511 West Harrison
Des Plaines, Illinois 60016

It should be noted that this permit has been revised so as to include operation of the equipment described in Construction Permit 14010026.

If you have any questions on this, please call Jocelyn Stakely at 217/785-1705.

Raymond E. Pilapil
Acting Manager, Permit Section
Division of Air Pollution Control

Date Signed: _____

REP:JRS:psj

cc: Illinois EPA, FOS Region 1
Lotus Notes

Attachment A - Emissions Summary

This attachment provides a summary of the maximum emission from the Corrugated Boxes Manufacturing Facility operating in compliance with the requirements of this federally enforceable permit. In preparing this summary, the Illinois EPA used the annual operating scenario which results in maximum emissions from such a plant. The resulting maximum emissions are well below the levels (e.g., 100 tons/year for VOM, 10 tons/year for any single HAP, and 25 tons/year for any combination of such HAP) at which this source would be considered a major source for purposes of the Clean Air Act Permit Program. Actual emissions from this source will be less than predicted in this summary to the extent that material is handled, and control measures are more effective than required in this permit.

| <u>Emission Unit</u> | E M I S S I O N S (Tons/Year) | | | | | Single | Combined |
|----------------------|-------------------------------|-----------------------|-----------|-----------------------|------------|------------|------------|
| | <u>CO</u> | <u>NO_x</u> | <u>PM</u> | <u>SO₂</u> | <u>VOM</u> | <u>HAP</u> | <u>HAP</u> |
| Ink Usage | | | | | 11.00 | | |
| High-VOM Glue Usage | | | | | 1.00 | | |
| Low-VOM Glue Usage | | | | | 10.00 | | |
| Boiler | 10.57 | 12.58 | 0.96 | 0.08 | 0.70 | | |
| Starch Silo with | | | | | | | |
| Baghouses | ----- | ----- | 0.44 | ----- | ----- | ----- | ----- |
| Totals: | 10.57 | 12.58 | 1.35 | 0.08 | 22.70 | 9.00 | 22.50 |

JRS:psj